

PRO MP245PG E14

SLIM, SLEEK, SMOOTH





SPECIFICATIONS

面板尺寸	23.8"
曲面螢幕	Flat
最佳解析度	1920 x 1080 (FHD)
更新頻率	144Hz
反應時間	1ms (MPRT) / 4ms (GTG)
面板類型	IPS
亮度	300 cd/m2
可視角度	178°(H) / 178°(V)
螢幕比例	16:9
靜態對比度	1500:1
顯示區域(MM)	527.04(H) x 296.46(V)
像素 (H X V)	0.2745(H) x 0.2745(V)
表面處理	Anti-glare
色彩顯示	16.7M, 8 bits (6 bits + FRC)
影像連接埠	1x HDMI™ 2.0 (FHD@144Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA)
DCR	100000000:1
Signal Frequency	52.85~158.54 KHz(H) / 48~144 Hz(V)
音頻接孔	1x Line-in 1x Headphone-out
th. → t+ tot →t	Yes
肯辛頓鎖孔	162
SPEAKER	2W x2
SPEAKER	2W x2
SPEAKER VESA安装	2W x2 100 x 100 mm
SPEAKER VESA安装 電源規格	2W x2 100 x 100 mm Internal Power Board
SPEAKER VESA安装 電源規格 HDR SUPPORT	2W x2 100 x 100 mm Internal Power Board HDR Ready
SPEAKER VESA安装 電源規格 HDR SUPPORT 電源輸入	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz
SPEAKER VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角)	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20°
SPEAKER VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整 (仰角) 調整 (左右旋轉)	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20° -45°~45°
SPEAKER VESA安装 電源規格 HDR SUPPORT 電源輸入 調整 (仰角) 調整 (左右旋轉) 調整 (垂直旋轉)	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20° -45°~45° -90°~90°
SPEAKER VESA安装 電源規格 HDR SUPPORT 電源輸入 調整 (仰角) 調整 (左右旋轉) 調整 (垂直旋轉) 調整 (高度)	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20° -45°~45° -90°~90° 0~130 mm
SPEAKER VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整 (仰角) 調整 (左右旋轉) 調整 (垂直旋轉) 調整 (高度) Webcam	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20° -45°~45° -90°~90° 0~130 mm N/A
SPEAKER VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角) 調整(左右旋轉) 調整(垂直旋轉) 調整(高度) Webcam Activated Range	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20° -45°~45° -90°~90° 0~130 mm N/A 48~144Hz Adaptive-Sync
SPEAKER VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角) 調整(左右旋轉) 調整(垂直旋轉) 調整(高度) Webcam Activated Range 動態刷新率技術 Dimension with Stand (W x D x	2W x2 100 x 100 mm Internal Power Board HDR Ready 100~240V, 50/60Hz -5° ~ 20° -45°~45° -90°~90° 0~130 mm N/A 48~144Hz Adaptive-Sync 539.36 x 226.93 x 519.29 mm

FEATURES



IPS Grade Panel

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best while creating your own on-line video



Perfect Edge

Set-up multi-display immensely with the 4-side edgeless design and enjoy the wider and more immersive view.



144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



EyesErgo

EyesErgo An eye care solution designed with ergonomics in mind.



Eye-Q Check

Help have self-check eyes & remind to take a rest while using the monitor for a long time.



Adjustable stand

Adjust the stand to the angle that is most suitable for you to keep yourself work comfortably.



Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.



Mini-PC Mountable

The mini PC can be conveniently mounted behind the monitor, keeping your desk clutter-free and organized.





PRO MP245PG E14

SLIM, SLEEK, SMOOTH

重量	5.25 kg (11.57 lbs) / 7.51 kg (16.56 lbs)
CARTON DIMENSION (W X D X H)	600 x 125 x 500 mm (23.62 x 4.92 x 19.69 inch)
認證	CB/CE Energy Star
ACCESSORIES	1x HDMI™ Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 4x Stand Screw, 1x VESA Plate, 4x VESA Plate Screw
備註	HDMI™: 1920 x 1080 (Up to 144Hz) DisplayPort: 1920 x 1080 (Up to 144Hz) D-Sub (VGA): (Up to 60Hz) Support: HDMI™ CEC/ MSI Power Link; Non Support: KVM, PIP/PBP

CONNECTIONS



- 1. 5-way Navigator
- 2. AC-in
- 3. 1x DisplayPort 1.4a
- 4. 1x HDMI[™] 2.0 (FHD@144Hz)
- 5. 1x D-Sub (VGA)
- 6. 1x Line-in
- 7. 1x Headphone-out
- 8. Kensington Lock