

PRO MP273L E14

SLIM, SLEEK, SMOOTH







SPECIFICATIONS

面板尺寸	27"
曲面螢幕	Flat
最佳解析度	1920 x 1080 (FHD)
更新頻率	144Hz
反應時間	1ms (MPRT) / 4ms (GtG)
面板類型	IPS
亮度	250 cd/m2
可視角度	178°(H) / 178°(V)
螢幕比例	16:9
靜態對比度	1500:1
sRGB	102% (CIE 1976)
顯示區域(MM)	597.888(H) x 336.312(V)
像素 (H X V)	0.3114(H) x 0.3114(V)
表面處理	Anti-glare
色彩顯示	16.7M, 8 bits (6 bits + FRC)
影像連接埠	1x HDMI™ 2.0 (FHD@144Hz) 1x D-Sub (VGA)
DCR	100000000:1
Signal Frequency	53.8~143.2 KHz(H) / 48~144 Hz(V)
肯辛頓鎖孔	Yes
肯辛頓鎖孔 SPEAKER	Yes N/A
SPEAKER	N/A
SPEAKER Audio Interface	N/A
SPEAKER Audio Interface VESA安裝	N/A N/A 100 x 100 mm
SPEAKER Audio Interface VESA安裝 電源規格	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready
SPEAKER Audio Interface VESA安装 電源規格 HDR SUPPORT 電源輸入	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角)	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20°
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角) 調整(左右旋轉)	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角) 調整(左右旋轉)	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A N/A
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整 (仰角) 調整 (左右旋轉) 調整 (垂直旋轉)	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A N/A N/A
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整 (仰角) 調整 (左右旋轉) 調整 (垂直旋轉) 調整 (高度) Webcam	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A N/A N/A N/A
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仰角) 調整(在右旋轉) 調整(垂直旋轉) 調整(高度) Webcam Activated Range	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A N/A N/A N/A N/A N/A N/A N/A
SPEAKER Audio Interface VESA安装 電源規格 HDR SUPPORT 電源輸入 調整(仰角) 調整(在右旋轉) 調整(垂直旋轉) 調整(高度) Webcam Activated Range 動態刷新率技術 Dimension with Stand (W x D x	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A N/A N/A N/A N/A 48~144Hz Adaptive-Sync 613.49 x 201.00 x 437.52 mm (24.15 x 1.96 x 14.27 inch)
SPEAKER Audio Interface VESA安裝 電源規格 HDR SUPPORT 電源輸入 調整(仲角) 調整(左右旋轉) 調整(直旋轉) 調整(高度) Webcam Activated Range 動態刷新率技術 Dimension with Stand (W x D x H) Dimension without Stand (W x D	N/A N/A 100 x 100 mm External Adaptor 12V 2.5A HDR Ready 100~240V, 50/60Hz -5° ~ 20° N/A N/A N/A N/A N/A Adaptive-Sync 613.49 x 201.00 x 437.52 mm (24.15 x 1.96 x 14.27 inch) 613.49 x 49.69 x 362.46 mm

FEATURES



144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



PS Grade Panel

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best while creating your own on-line video



EyesErgo

EyesErgo An eye care solution designed with ergonomics in mind.



Anti-Flicker technology

MSI Anti-Flicker technology provides a very comfortable viewing experience by reducing the amount of screen flicker.



Less Blue Light

Effectively reduce blue light which could cause serious long-term damage to your eyes.



Eye-Q Check

Help have self-check eyes & remind to take a rest while using the monitor for a long time.



VESA Mountable

To be mounted on the wall of your office & home with a VESA standard design which can make it completely invisible on a desk.



MSI Power Link

A desktop PC can be powered by an MSI-selected monitor through MSI Power Link technology, enabling the most convenient user experience.



PRO MP273L E14

SLIM, SLEEK, SMOOTH

CARTON DIMENSION (W X D X H)	672 x 88 x 508 mm (26.73 x 2.72 x 20 inch)
ACCESSORIES	1x HDMI™ Cable (2.0b), 1x Power Adaptor, 1x Quick Guide
備註	HDMI™: 1920 x 1080 (Up to 144Hz) D-Sub (VGA): 1920 x 1080 (Up to 60Hz) Support: HDMI™ CEC/ MSI Power Link, FW Update; Non Support: KVM, PIP/PBP

CONNECTIONS



- 1. 5-way Navigator
- 2. 1x HDMI™ 2.0 (FHD@144Hz)
- 3. 1x D-Sub (VGA)
- 4. DC-in