



SPECIFICATIONS

Signal Frequency	72~216 KHz(H) / 48-144 Hz(V)
PANEL SIZE	27"
ADOBE RGB / DCI-P3 / SRGB	87% / 93% / 121% (CIE1976)
PANEL RESOLUTION	2560 x 1440 (WQHD)
REFRESH RATE	144Hz
RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
PANEL TYPE	IPS
VIEWING ANGLE	178°(H) / 178°(V)
ASPECT RATIO	16:9
CONTRAST RATIO	1500:1
PIXEL PITCH (H X V)	0.2331(H) x 0.2331(V)
HDR SUPPORT	HDR Ready
ACTIVE DISPLAY AREA (MM)	597.736(H) x 335.664(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M
USB Ports	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
COLOR BIT	8 bits (6 bits + FRC)
VIDEO PORTS	2x HDMI™ 2.0b (WQHD@144Hz) 1x DisplayPort 1.2a 1x Type-C (DP alt.) w/ 65W PD
AUDIO PORTS	1x Headphone-out
KENSINGTON LOCK	Yes
SPEAKER	3W x2
BRIGHTNESS (NITS)	300 cd/m2
VESA MOUNTING	75 x 75 mm
POWER TYPE	Internal Power Board
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
ADJUSTMENT (TILT)	-5° ~ 20°
Dimension with Stand (W x D x H)	613.49 x 200.81 x 401.72 mm (24.15 x 7.91 x 15.82 inch)
ADJUSTMENT (SWIVEL)	-30° ~ 30°
Dimension without Stand (W x D x H)	613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch)
ADJUSTMENT (PIVOT)	-90° ~ 90°
ADJUSTMENT (HEIGHT)	0 ~ 110 mm

FEATURES



IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



EyesErgo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



Circular Polarization

Converts harsh digital rays into soft, naturally-polarized light to prevent eye strain and maximize visual comfort.



144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



Type C 65W Power Delivery

Built-in an USB Type-C connection with 65W power delivery allows you to effortlessly connect to and charge your devices




Delta-E (ΔE) ≤ 2

Factory pre-calibrated to guarantee a truly expressive hues and color accuracy.

CARTON DIMENSION (W X D X H)	613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch)
WEIGHT (NW / GW)	6.4 kg (14.11 lbs) / 10.1 kg (22.27 lbs)
NOTE	HDMI™: 2560 x 1440 (Up to 144Hz) DisplayPort: 2560 x 1440 (Up to 144Hz) Type-C: 2560 x 1440 (Up to 144Hz) Delta-E (ΔE) ≤ 2 Support: HDMI CEC/ MSI Power Link, KVM 1.0, FW Update, PI App, M-Mate App; Non-Support: PIP/PBP
ACCESSORIES	1x HDMI Cable (2.0b), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, Color Report

CONNECTIONS



1. 5-Way Navi-Key
2. 1x Headphone-out
3. 2x HDMI™ 2.0b (FHD@144Hz)
4. 1x DisplayPort 1.2a
5. 1x Type-C (DP alt.) w/ 65W PD
6. 1x USB 5Gbps Type-B
7. 2x USB 5Gbps Type-A
8. AC-in
9. Kensington-Lock