

PRO MP275W E2

SLIM, SLEEK, SMOOTH







SPECIFICATIONS

PANEL RESOLUTION 1920 x 1080 (FHD) REFRESH RATE 120Hz RESPONSE TIME 1ms (MPRT) / 4ms (GtG) PANEL TYPE IPS VIEWING ANGLE 178° (H) / 178° (V) ASPECT RATIO 16:9 CONTRAST RATIO 1500:1 PIXEL PITCH (H X V) 0.3114 (H) x 0.3114 (V) HDR Ready sRGB ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) VIDEO PORTS 1x HDMI™ 2.0 (FHD@120Hz) 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSIO	PANEL SIZE	27"
RESPONSE TIME 1ms (MPRT) / 4ms (GtG) PANEL TYPE IPS VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1500:1 PIXEL PITCH (H X V) 0.3114 (H) x 0.3114 (V) HDR Ready sRGB ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) 1x Headphone-out AUDIO PORTS 1x Headphone-out 1x Line-in 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON	PANEL RESOLUTION	1920 x 1080 (FHD)
PANEL TYPE IPS VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1500:1 PIXEL PITCH (H X V) 0.3114 (H) x 0.3114 (V) HDR Ready HDR Ready SRGB 116% ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x D:SubjelayPort 1.2a 1x D-Sub (VGA) 1x Headphone-out 1x Line-in 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch)	REFRESH RATE	120Hz
VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1500:1 PIXEL PITCH (H X V) 0.3114 (H) x 0.3114 (V) HDR Ready SRGB ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) 1x Headphone-out 1x Line-in 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync DOWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) CEPTIFICATES CB/CE	RESPONSE TIME	1ms (MPRT) / 4ms (GtG)
ASPECT RATIO CONTRAST RATIO PIXEL PITCH (H X V) HDR SUPPORT SRGB 116% ACTIVE DISPLAY AREA (MM) SURFACE TREATMENT DISPLAY COLORS COLOR BIT VIDEO PORTS AUDIO PORTS AUDIO PORTS ENSINGTON LOCK SPEAKER BRIGHTNESS (NITS) VESA MOUNTING POWER TYPE DYNAMIC REFRESH RATE TECHNOLOGY POWER INPUT ADJUSTMENT (TILT) DIMENSION (W X H X D) CERTIFICATES CONSTITUTE (1500) 1500:1 1500:1 16:9 0.3114 (H) x 0.3114 (V) HDR Ready 16:9 0.3114 (H) x 0.3114 (V) HDR Ready SPISSION 10: 16:9 0.3114 (H) x 0.3114 (V) HDR Ready 16:9 16:	PANEL TYPE	IPS
CONTRAST RATIO 1500:1 PIXEL PITCH (H X V) 0.3114 (H) x 0.3114 (V) HDR Ready HDR Ready SRGB 116% ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) 1x Headphone-out AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs)	VIEWING ANGLE	178°(H) / 178°(V)
PIXEL PITCH (H X V) HDR SUPPORT SRGB 116% ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT DISPLAY COLORS COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out 1x Line-in KENSINGTON LOCK SPEAKER 2x 2W BRIGHTNESS (NITS) VESA MOUNTING POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY POWER INPUT ADJUSTMENT (TILT) DIMENSION (W X H X D) CARTON DIMENSION (W X H X D) CERTIFICATES CB/CE CERTIFICATES CB/CE ACTIVE DIMENSION (W X H X D) 0.3114 (H) x 0.3114 (V) HDR Ready 0.3114 (H) x 0.3114 (V) HDR Ready 0.3114 (H) x 0.3114 (V) HDR Ready 9.3114 (H) x 0.3114 (V) HDR Ready 9.316 (b) x 336.312 (V) Surface 16% Athical Ready 16.7M 20. (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) 1x Headphone-out 1x Line-in 1x Line-in 1x Line-in 1x Line-in 1x Line-in 1x Headphone-out 1x Line-in 1x Headphone-out 1x Line-in 1x Headphone-out 1x Line-in 1x Headphone-out 1x Line-in 4 Headphone-out 1x Line-in 1x Headphone-out 1x Headphone-out	ASPECT RATIO	16:9
HDR SUPPORT sRGB ACTIVE DISPLAY AREA (MM) SURFACE TREATMENT DISPLAY COLORS COLOR BIT VIDEO PORTS AUDIO PORTS KENSINGTON LOCK SPEAKER BRIGHTNESS (NITS) VESA MOUNTING POWER TYPE DYNAMIC REFRESH RATE TECHNOLOGY POWER INPUT ADJUSTMENT (TILT) DIMENSION (W X H X D) CARTON DIMENSION (W X H X D) CERTIFICATES CSUR AND S 116% 597.888 (H) x 336.312 (V) Anti-glare 16.7M Anti-glare 16.7M 2 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x HDMI	CONTRAST RATIO	1500:1
SRGB 116% ACTIVE DISPLAY AREA (MM) 597.888 (H) x 336.312 (V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CEPTIFICATES CB/CE	PIXEL PITCH (H X V)	0.3114 (H) x 0.3114 (V)
ACTIVE DISPLAY AREA (MM) SURFACE TREATMENT DISPLAY COLORS COLOR BIT 16.7M	HDR SUPPORT	HDR Ready
SURFACE TREATMENT Anti-glare DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CEPTIFICATES CB/CE	sRGB	116%
DISPLAY COLORS 16.7M COLOR BIT 8 bits (6 bits + FRC) 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) 1x Headphone-out AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE Adaptive-Sync TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CEPTIEICATES CB/CE	ACTIVE DISPLAY AREA (MM)	597.888 (H) x 336.312 (V)
COLOR BIT 8 bits (6 bits + FRC) VIDEO PORTS 1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	SURFACE TREATMENT	Anti-glare
VIDEO PORTS 1x HDMI™ 2.0 (FHD@120Hz) 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CEPTIFICATES CB/CE	DISPLAY COLORS	16.7M
VIDEO PORTS 1x DisplayPort 1.2a 1x D-Sub (VGA) AUDIO PORTS 1x Headphone-out 1x Line-in KENSINGTON LOCK Yes SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	COLOR BIT	8 bits (6 bits + FRC)
1x Line-in	VIDEO PORTS	1x DisplayPort 1.2a
SPEAKER 2x 2W BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CEPTIFICATES CB/CE	AUDIO PORTS	
BRIGHTNESS (NITS) 300 cd/m² VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	KENSINGTON LOCK	Yes
VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	SPEAKER	2x 2W
POWER TYPE Internal Power Board DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	BRIGHTNESS (NITS)	300 cd/m ²
DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	VESA MOUNTING	100 x 100 mm
TECHNOLOGY Adaptive-Sync POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	POWER TYPE	Internal Power Board
ADJUSTMENT (TILT) -5° ~ 20° DIMENSION (W X H X D) CARTON DIMENSION (W X H X D) G88 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) CERTIFICATES CB/CE		Adaptive-Sync
DIMENSION (W X H X D) 611.9 x 447.7 x 206.8 mm (24.09 x 17.63 x 8.14 inch) CARTON DIMENSION (W X H X D) 688 x 505 x 128 mm (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	POWER INPUT	100~240V, 50~60Hz
CARTON DIMENSION (W X H X D) (24.09 x 17.63 x 8.14 inch) (24.09 x 17.63 x 8.14 inch) (27.09 x 19.89 x 5.04 inch) WEIGHT (NW / GW) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CB/CE	ADJUSTMENT (TILT)	-5° ~ 20°
WEIGHT (NW / GW) (27.09 x 19.89 x 5.04 inch) 3.66 kg (8.07 lbs) / 6.54 kg (14.42 lbs) CERTIFICATES CB/CE	DIMENSION (W X H X D)	
CERTIFICATES (NW / GW) Ibs CB/CE	CARTON DIMENSION (W X H X D)	
CERTIFICATES	WEIGHT (NW / GW)	j , , , , , , , , , , , , , , , , , , ,
	CERTIFICATES	,

FEATURES



IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



Set-up multi-display immensely with the 4-side edgeless design and enjoy the wider and more immersive view.



120Hz High Refresh Rate

120 Hz Enjoy the high-quality entertainment with a smoother and flickerfree images.



EyesErgo

EyesErgo An eye care solution designed with ergonomics in mind.



Eye-Q Check

Help have self-check eyes & remind to take a rest while using the monitor for a long time.



Accessory Slot Design

Enjoy a clean table with the accessory slot design where you can put MSI Pen or Smartphone, and you will not miss important messages anymore.



Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.



VESA Mountable

To be mounted on the wall of your office & home with a VESA standard design which can make it completely invisible on a desk.



PRO MP275W E2

SLIM, SLEEK, SMOOTH

Compatibility	PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook *All trademarks and the registered trademarks are the property of their respective owners.
NOTE	HDMI™: 1920 x 1080 (Up to 120Hz) DisplayPort: 1920 x 1080 (Up to 120Hz) D-Sub (VGA): 1920 x 1080 (Up to 60Hz) HDMI™ CEC Support *sRGB follow CIE1976 Standard

CONNECTIONS



- 1. 1x DisplayPort 1.2a
- 2. 1x HDMI[™] 2.0 (FHD@120Hz)
- 3. 1x D-Sub (VGA)
- 4. 1x Line-in
- 5. 1x Headphone-out
- 6. 1x AC-in
- 7. 1x Kensington Lock
- 8. 1x 5-Way Navigator