

# **SPATIUM M371 NVMe M.2**







## **SPECIFICATIONS**

| Model Name                       | SPATIUM M371 NVMe M.2   |         |         |
|----------------------------------|---|---------|---------|
| Capacity                         | 500GB   | 1TB     | 2TB     |
| Controller                       | PHISON E13T   |         |         |
| Flash Memory                     | 3D NAND   |         |         |
| Form Factor                      | M.2 2280  |         |         |
| Interface                        | PCle Gen3x4, NVMe 1.3   |         |         |
| Compatibility                    | PCle Gen3 / Gen2 / Gen1   |         |         |
| Dimensions                       | 80.00mm (L) x 22.00mm (W) x 2.15mm (H)  |         |         |
| Sequential Read up to (MB/s)     | 2200  | 2350    | 2350    |
| Sequential Write up to (MB/s)    | 1150  | 1700    | 1900    |
| Random Read 4KB up to (IOPS)     | 60,000  | 90,000  | 135,000 |
| Random Write 4KB up to (IOPS)    | 200,000   | 280,000 | 350,000 |
| Maximum Operating Power (W)      | 2.4   | 3.2     | 3.4     |
| Idle Power PS3 (mW)              | 30  |         |         |
| Low Power L1.2 (mW)              | 5   |         |         |
| Operating Temperatures           | 0°C - 70°C  |         |         |
| Storage Temperatures             | -40°C - 85°C  |         |         |
| Terabytes Written (TBW)          | 110   | 210     | 480     |
| Mean Time Between Failure (MTBF) | Up to 1,500,000 Hours   |         |         |
| Limited Warranty                 | 5 Years, or the coverage for the maximum TBW as stated, whichever comes first.  |         |         |
| Advanced Features                | TRIM (Performance Optimization, OS<br>Support required)<br>SMART (Self-Monitoring, Analysis and<br>Reporting Technology)<br>LDPC (Low Density Parity Check) ECC<br>Algorithm<br>End to End Data Path Protection<br>APST (Autonomous Power State Transition)<br>Pyrite (Encryption, Data Security) |         |         |

# **FEATURES**



#### **Blazing Speeds**

Optimized for the PCIe Gen3 interface.



#### 3D NAND Flash

3D NAND Flash technology brings dense storage in a compact design and allows storage capacities up to 2TB.



## Security & Reliability

Built-in data security and error-correction capabilities extend the longevity of the NAND flash storage.



#### **MSI Center**

Migrate data with backup & restore functionality, monitor drive health and performance metrics in real-time in MSI Center.



### **5 Years Warranty**

MSI stands by the quality and reliability of their SSD's with a 5 year limited warranty.