




FEATURES



Blazing Speeds

Optimized for the PCIe Gen3 interface.



3D NAND Flash

3D NAND Flash technology brings dense storage in a compact design and allows storage capacities up to 2TB.



Security & Reliability

Built-in data security and error-correction capabilities extend the longevity of the NAND flash storage.



Low Latency Gaming

Enjoy minimal latency in smooth gameplay and loading games with optimized high-performance bandwidth and throughput.



Nonstop Creativity Booster

Keep up nonstop productivity by opening up images, movies, documents, and heavy-duty applications at lightning speeds.



MSI Center

Monitor SSD health status and key performance metrics in real time via MSI Center for stable and reliable system performance.



Optimal M.2 SSD

Designed in the M.2 2280 form factor, MSI SSDs are easy to install into external enclosures, desktops, or laptops.



5 Years Warranty

MSI stands by the quality and reliability of their SSD's with a 5 year comprehensive warranty.

SPECIFICATIONS

Model Name	SPATIUM M390 NVMe M.2			
Capacity	250GB	500GB	1TB	2TB
Controller	PHISON E15T			
Flash Memory	3D NAND			
Form Factor	M.2 2280			
Interface	PCIe Gen3x4, NVMe 1.4			
Compatibility	PCIe Gen3 / Gen2 / Gen1			
Dimensions	80.00mm (L) x 22.00mm (W) x 2.15mm (H)			
Sequential Read up to (MB/s)	3300			
Sequential Write up to (MB/s)	1200	2300	3000	3000
Random Read 4KB up to (IOPS)	150,000	300,000	420,000	420,000
Random Write 4KB up to (IOPS)	300,000	550,000	550,000	550,000
Maximum Operating Power (W)	3.2	3.2	4.0	4.3
Idle Power PS3 (mW)	30			
Low Power L1.2 (mW)	5			
Operating Temperatures	0°C - 70°C			
Storage Temperatures	-40°C - 85°C			
Terabytes Written (TBW)	150	200	400	1200
Mean Time Between Failure (MTBF)	Up to 1,500,000 Hours			
Limited Warranty	5 Years, or the coverage for the maximum TBW as stated, whichever comes first.			
Advanced Features	TRIM (Performance Optimization, OS support required) SMART (Self-Monitoring, Analysis and Reporting Technology) LDPC (Low Density Parity Check) ECC Algorithm End to End Data Path Protection APST (Autonomous Power State Transition) Pyrite (Encryption, Data Security)			

TEST CONFIGURATION

Sequential and random performance, and power consumption were measured with the system configurations listed below. All performance data was tested with the SSD as a secondary drive.

Interface	PCIe Gen3x4
Operating System	Windows 10 Pro 21H1 OS Build 19043.928
CPU	11 th Gen Intel Core i7-11700KF @3.6GHz
Memory	Samsung DDR4-2400 8G
Chipset	MSI MPG Z590 GAMING CARBON WIFI
Test Program	Crystal Diskmark 8.01, ATTO Disk Benchmark V4.01.0f1, IO Meter v1.1.0