

# SPATIUM M480 PRO PCIe 4.0 NVMe M.2 HS




## FEATURES



### Aluminum Heatsink

Bronze-colored aluminum heatsink with a stacked fin structure maximizes performance under heavy loads.



### Blazing Speeds

Optimized for the PCIe Gen4 interface.



### 3D NAND

The 3D NAND flash technology brings dense storage in a compact design and allows storage capacities up to 4TB.



### Security & Reliability

Built-in data security and error-correction capabilities extend the longevity of the NAND flash storage.



### Low Latency Gaming

Enjoy minimal latency in smooth gameplay and loading games with optimized high-performance bandwidth and throughput.



### Nonstop Creativity Booster

Keep up nonstop productivity by opening up images, movies, documents, and heavy-duty applications at lightning speeds.



### MSI Center

Monitor SSD health status and key performance metrics in real time via MSI Center for stable and reliable system performance.



### Optimal M.2 SSD

Designed in the M.2 2280 form factor, MSI SSDs are easy to install into external enclosures, desktops, or laptops.



### 5 Years Warranty

MSI stands by the quality and reliability of their SSD's with a 5 year limited warranty.

## SPECIFICATIONS

<b>Model Name</b>	SPATIUM M480 PRO PCIe 4.0 NVMe M.2 HS		
<b>Capacity</b>	1TB	2TB	4TB
<b>Controller</b>	PHISON E18		
<b>Flash Memory</b>	3D NAND		
<b>DRAM Cache</b>	1GB DDR4	2GB DDR4	2GB DDR4
<b>Form Factor</b>	M.2 2280		
<b>Interface</b>	PCIe Gen4x4, NVMe 1.4		
<b>Compatibility</b>	PCIe Gen4 / Gen3 / Gen2 / Gen1		
<b>Dimensions</b>	80.40mm (L) x 23.00mm (W) x 20.40mm (H)		
<b>Sequential Read up to (MB/s)</b>	7400		
<b>Sequential Write up to (MB/s)</b>	6000	7000	7000
<b>Random Read 4KB up to (IOPS)</b>	750,000	1,000,000	1,000,000
<b>Random Write 4KB up to (IOPS)</b>	1,000,000		
<b>Maximum Operating Power (W)</b>	9.5	10.5	11.3
<b>Idle Power PS3 (mW)</b>	40	45	50
<b>Low Power L1.2 (mW)</b>	3		
<b>Operating Temperatures</b>	0°C - 70°C		
<b>Storage Temperatures</b>	-40°C - 85°C		
<b>Terabytes Written (TBW)</b>	700	1400	3000
<b>Mean Time Between Failure (MTBF)</b>	Up to 1,600,000 Hours		
<b>Limited Warranty</b>	5 Years, or the coverage for the maximum TBW as stated, whichever comes first.		
<b>Advanced Features</b>	TRIM (Performance Optimization, OS Support required) SMART (Self-Monitoring, Analysis and Reporting Technology) LDPC (Low Density Parity Check) ECC Algorithm End to End Data Path Protection APST (Autonomous Power State Transition) AES256/Pyrite (Encryption, Data Security)		

## TEST CONFIGURATION

Sequential and random performance, and power consumption were measured with the system configurations listed below. All performance data was tested with the SSD as a secondary drive.

<b>Interface</b>	PCIe Gen4x4
<b>Operating System</b>	Windows 11 Pro 22H2 OS Build 22621.1105
<b>CPU</b>	AMD Ryzen 9 7950X 16-Core @4.60 GHz
<b>Memory</b>	Kingston DDR5-4800 16G x2
<b>Chipset</b>	MSI MEG X670E ACE
<b>Test Program</b>	Crystal Diskmark 8.04c, ATTO Disk Benchmark V4.01.0f1, IO Meter v1.1.0