




SPECIFICATIONS

| | |
|-----------------------------------|---|
| Model Name | GeForce RTX™ 4060 8G GAMING DUKE 2X |
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 4060 |
| Interface | PCI Express® Gen 4 x16 (uses x8) |
| Cores | 3072 Units |
| Core Clocks | Extreme Performance: 2475 MHz (MSI Center) Boost: 2460 MHz |
| Memory Speed | 17 Gbps |
| Memory | 8GB GDDR6 |
| Memory Bus | 128-bit |
| Output | DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a) |
| HDCP Support | Y |
| Power consumption | 115 W |
| Power connectors | 8-pin x 1 |
| Recommended PSU | 550 W |
| Card Dimension (mm) | 240 x 122 x 45 mm |
| WEIGHT (CARD) | 682 g |
| DirectX Version Support | 12 Ultimate |
| OpenGL Version Support | 4.6 |
| Maximum Displays | 4 |
| G-SYNC® technology | Y |
| Digital Maximum Resolution | 7680 x 4320 |

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.




Ring-Shaped Fan Design

Ring arcs link the tips of all of the fan blades together to focus airflow and increase air pressure into the heatsink.



Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Custom PCB

The custom PCB has been engineered with hardened circuits and optimized trace routing for performance and reliability.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.