


SPECIFICATIONS

| | |
|---------------------------------------|--|
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 4070 SUPER |
| Núcleos | 7168 Units |
| Memória | 12GB GDDR6X |
| Recommended PSU | 650 W |
| Barramento Padrão | PCI Express® Gen 4 |
| Interface de Memória | 192-bit |
| Velocidade Clock Central (MHz) | Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz |
| Velocid. Clock Memória (MHz) | 21 Gbps |
| Máximo de Monitores | 4 |
| Tecnologia G-SYNC™ | Y |
| Saídas | DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI 2.1a) |
| Suporte HDCP | Y |
| Consumo de energia (W) | 245W |
| Resolução máx. Digital | 7680 x 4320 |
| Conectores de energia | 16-pin x 1 |
| Suporte Versão DirectX | 12 Ultimate |
| Suporte Versão OpenGL | 4.6 |
| Dimensões(mm) | 307 x 125 x 46 mm |
| Peso | 972 g / 1585 g |

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.