

SPECIFICATIONS

Graphics Processing Unit	NVIDIA® GeForce RTX™ 4070 SUPER
Núcleos	7168 Units
Memória	12GB GDDR6X
Recommended PSU	650 W
Barramento Padrão	PCI Express® Gen 4
Interface de Memória	192-bit
Velocidade Clock Central (MHz)	Extreme Performance: 2520 MHz (MSI Center) Boost: 2505 MHz
Velocid. Clock Memória (MHz)	21 Gbps
Máximo de Monitores	4
Tecnologia G-SYNC™	Y
Consumo de energia (W)	220 W
Suporte HDCP	Y
Saídas	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
Resolução máx. Digital	7680 x 4320
Conectores de energia	16-pin x 1
Suporte Versão DirectX	12 Ultimate
Suporte Versão OpenGL	4.6
Dimensões(mm)	242 x 125 x 43 mm
Peso	680 g / 998 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

Dual Fan



Two fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 4.0




A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.

Copper Baseplate



A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.

Core Pipe



Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.

Reinforcing Backplate



The reinforcing backplate features a flow-through design that provides additional ventilation.

Zero Frozr



The fans completely stop when temperatures are relatively low, eliminating all noise.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.