

SPECIFICATIONS

Graphics Processing Unit	NVIDIA® GeForce RTX™ 4070 Ti SUPER
Núcleos	8448 Units
Memória	16GB GDDR6X
Recommended PSU	700 W
Barramento Padrão	PCI Express® Gen 4
Interface de Memória	256-bit
Velocidade Clock Central (MHz)	Extreme Performance: 2685 MHz (MSI Center) Boost: 2670 MHz
Velocid. Clock Memória (MHz)	21 Gbps
Máximo de Monitores	4
Tecnologia G-SYNC™	Y
Consumo de energia (W)	285 W
Saídas	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI 2.1a)
Suporte HDCP	Y
Resolução máx. Digital	7680 x 4320
Conectores de energia	16-pin x 1
Suporte Versão DirectX	12 Ultimate
Suporte Versão OpenGL	4.6
Dimensões(mm)	307 x 125 x 51 mm
Peso	1094 g / 1676 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.




MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.