



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G CYCLONE
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060
Núcleos	3840 Units
Memória	8GB GDDR7
Recommended PSU	550 W
Barramento Padrão	PCI Express® Gen 5 X16 (uses x8)
Interface de Memória	128-bit
Velocidade Clock Central (MHz)	Extreme Performance: 2512 MHz (MSI Center) Boost: 2497 MHz
Velocid. Clock Memória (MHz)	28 Gbps
Máximo de Monitores	4
Tecnologia G-SYNC™	Y
Saídas	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Suporte HDCP	Y
Consumo de energia (W)	145 W
Resolução máx. Digital	7680 x 4320
Conectores de energia	8-pin x 1
Suporte Versão DirectX	12 Ultimate
Suporte Versão OpenGL	4.6
Dimensões(mm)	161x125x42mm
Peso	451g / 761g

FEATURES



Advanced CYCLONE Cooling Design

The advanced circular thermal design dissipates heat from GPU and components effectively.



Custom Fan

The custom fan design with an optimized blade that generates more airflow and air pressure.



Solid Backplate

Increases toughness of the card to prevent bending while complementing the design.



Custom PCB

The custom PCB has been engineered with hardened circuits and optimized trace routing for performance and reliability.



Effective Thermal Padding

An abundance of thermal pads provide additional heat dissipation for board components.



MSI Center


The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

CONNECTIONS



1. DisplayPort
2. HDMI™