



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 Ti 16G GAMING TRIO OC
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060 Ti
Núcleos	4608 Units
Memória	16GB GDDR7
Recommended PSU	TBD
Barramento Padrão	PCI Express® Gen 5 x16 (uses x8)
Interface de Memória	128-bit
Velocidade Clock Central (MHz)	Extreme Performance: 2662 MHz (MSI Center) Boost: 2647 MHz
Velocid. Clock Memória (MHz)	28 Gbps
Máximo de Monitores	4
Tecnologia G-SYNC™	Y
Saídas	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Suporte HDCP	Y
Consumo de energia (W)	180 W
Resolução máx. Digital	7680 x 4320
Conectores de energia	16-pin x 1 (Recomendamos Fonte de Alimentação ATX 3.1)
Suporte Versão DirectX	12 Ultimate
Suporte Versão OpenGL	4.6
Dimensões(mm)	300 x 125 x 44 mm
Peso	844 g / 1384 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 4

Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.