




SPECIFICATIONS

Marketing Name	GeForce RTX™ 5090 32G SUPRIM OC
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5090
Núcleos	21760 Units
Memória	32GB GDDR7
Recommended PSU	1000 W
Barramento Padrão	PCI Express® Gen 5 x16
Interface de Memória	512-bit
Velocidade Clock Central (MHz)	Extreme Performance: 2497 MHz (MSI Center) Boost: 2482 MHz
Velocid. Clock Memória (MHz)	28 Gbps
Máximo de Monitores	4
Tecnologia G-SYNC™	Y
Saídas	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Suporte HDCP	Y
Consumo de energia (W)	575 W
Resolução máx. Digital	7680 x 4320
Conectores de energia	16-pin x 1 (Recomendamos Fonte de Alimentação ATX 3.1)
Suporte Versão DirectX	12 Ultimate
Suporte Versão OpenGL	4.6
Dimensões(mm)	359 x 150 x 76 mm
Peso	2840 g / 3695 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.




Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.




Optimized Heat Distribution - Core Pipe

Square-shaped Core Pipes maximize heat dissipation with the Vapor Chamber for superior cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.