



SPECIFICATIONS

| | |
|---------------------------------------|--|
| Marketing Name | GeForce RTX™ 5080 16G SHADOW 3X OC |
| Modèle | G5080-16S3C |
| Processeur graphique | NVIDIA® GeForce RTX™ 5080 |
| Cœurs | 10752 unités |
| Mémoire | 16 Go GDDR7 |
| Bus Mémoire | 256-bit |
| Fréquence du GPU | Performances extrêmes : 2655 MHz (MSI Center) Boost : 2640 MHz |
| Vitesse mémoire | 30 Gb/s |
| Nombre d'écrans supportés | 4 |
| Technologie G-SYNC™ | Oui |
| Résolution numérique maximum | 7680 x 4320 |
| Support du procédé HDCP | Oui |
| Bloc d'alimentation recommandé | 850 W |
| Connecteurs alimentation | 1 x 16 broches |
| Sorties | 3 x DisplayPort (v2.1b) 1 x HDMI™ (caractéristiques du HDMI™ 2.1b : jusqu'à 4K 480 Hz ou 8K 120 Hz avec DSC, Gaming VRR, HDR) |
| Version OpenGL | 4.6 |
| Dimensions | 303 x 121 x 49 mm |
| Poids | 1046 g / 1546 g |

FEATURES

OMRON 60+ MILLION OMRON SWITCHES



The crisp and reliable mechanical switches rated to last over 60 million clicks.

HIGH END PixArt PAW-3395 OPTICAL SENSOR



The PixArt PAW-3395 optical sensor is designed to dominate the game delivering up to 26,000 DPI, 650 IPS, and 50G acceleration.

Mystic Light



Персонализируйте свой компьютер с помощью 16,8 миллионов цветов / 31 эффекта, управляемых одним щелчком мыши!..

10G Super LAN + 5G LAN




Onboard 10G plus 5G LAN provide the next level network speed, secure networking with the fastest data throughput to deliver the best online gaming experience.

Lightning USB 40G



Featuring a built-in USB 4 port, it offers a lightning-fast 40Gbps transmission speed.

Display Kit Support



Providing the most convenient tool, the proper color & display mode to you while working with it everyday.

CONNECTIONS



1. DisplayPort
2. HDMI™