Senerated 2025-09-09, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.



GeForce RTX™ 5060 8G GAMING DUKE 3X OC PLUS







SPECIFICATIONS

* * * + + -	DCI F
总线接口	PCI Express [®] Gen 5 x16 (uses x8)
显示芯片	NVIDIA® GeForce RTX™ 5060
显存	8GB GDDR7
显存位宽	128-bit
核心频率	极致模式: 2550 MHz (MSI Center) Boost模式: 2535 MHz
显存速度	28 Gbps
最大屏幕输出数	4
G-SYNC® technology	Υ
最大分辨率	7680 x 4320
输出接口	DisplayPort x 3 (v2.1b) HDMI [™] x 1 (As specified in HDMI [™] 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP 支持	Y
建议电源 (W)	550 W
供电接口	8-pin x 1
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	325 x 121 x 45 mm
显卡尺寸 重量(显卡/包装盒)	325 x 121 x 45 mm 902 g / 1421 g

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



Circular Fan Design:

Circular arcs seamlessly connect the tips of the fan blades, concentrating airflow and boosting air pressure into the heatsink for enhanced thermal efficiency.



Solid Baseplate

A solid baseplate transfers heat from the GPU to all heat pipes for better cooling.



Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



Zero Frozr



The fans completely stop when temperatures are relatively low, eliminating all noise.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Take full control with the most recognized and widely used graphics card overclocking software in the world.