Senerated 2025-07-03, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.



GeForce RTX™ 5060 Ti 8G VENTUS 2X OC CLASSIC







SPECIFICATIONS

总线接口	PCI Express® Gen 5 x16 (uses x8)
显示芯片	NVIDIA® GeForce RTX™ 5060 Ti
显存	8GB GDDR7
显存位宽	128-bit
核心频率	极致模式: 2617 MHz (MSI Center) Boost模式: 2602 MHz
显存速度	28 Gbps
最大屏幕输出数	_4
G-SYNC® technology	Y
最大分辨率	7680 x 4320
	DisplayPort x 3 (v2.1b)
输出接口	HDMI [™] x 1 (As specified in HDMI [™] 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
输出接口 ————————————————————————————————————	
	480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP 支持	480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) Y
HDCP 支持 建议电源 (W)	480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) Y 600 W
HDCP 支持 建议电源 (W) 供电接口	480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) Y 600 W 8-pin x 1
HDCP 支持 建议电源 (W) 供电接口 DirectX 版本支持	480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) Y 600 W 8-pin x 1 12 Ultimate

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES



Two fans and a huge heatsink ensure a cool and quiet experience for you.



A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickelplated copper baseplate and transferred.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.