


SPECIFICATIONS

Model Name	GeForce RTX™ 4070 SUPER 12G VENTUS 2X OC
Cores	7168 Units
Memory	12GB GDDR6X
Standard sběrnice	PCI Express® Gen 4
Rozhraní paměti	192-bit
Takt jádra (MHz)	Extreme Performance: 2520 MHz (MSI Center) Boost: 2505 MHz
Takt paměti (MHz)	21 Gbps
Max připojených displejů	4
HDCP podpora	Y
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
Doporučený výkon zdroje (W)	650 W
Digital Maximum Resolution	7680 x 4320
Napájecí kabely	16-pin x 1
Podpora DirectX verze	12 Ultimate
Podpora OpenGL verze	4.6
Rozměry (mm)	242 x 125 x 43 mm
Váha (g)	680 g / 998 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Backplate

A clean-looking backplate reinforces the length of the card.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.