




SPECIFICATIONS

Model Name	GeForce RTX™ 4070 Ti SUPRIM 12G
Cores	7680 Units
Memory	12GB GDDR6X
Standard sběrnice	PCI Express® Gen 4
Rozhraní paměti	192-bit
Takt jádra (MHz)	Extreme Performance: 2760 MHz (MSI Center) Boost: 2745 MHz (GAMING & SILENT Mode)
Takt paměti (MHz)	21 Gbps
Max připojených displejů	4
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (supports 4K 120Hz HDR and 8K 60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a)
HDCP podpora	Y
Doporučený výkon zdroje (W)	750 W
Digital Maximum Resolution	7680x4320
Napájecí kabely	16-pin x 1
Podpora DirectX verze	12 Ultimate
Podpora OpenGL verze	4.6
Rozměry (mm)	338 x 142 x 73 mm
Váha (g)	2019g / 3224g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

The CNC machined nickel-plated copper base captures heat from the GPU and the memory then rapidly transfers it to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Air Antegrade Fin

A section of V-shape heatsink and side-fins work to refocus air resistance at the passthrough.



Aluminum Backplate

Thermal pads beneath the sturdy metal backplate provide additional cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.