



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G SHADOW 2X OC
Model Name	G5060-8S2C
Cores	3840 Units
Memory	8GB GDDR7
Standard sběrnice	PCI Express® Gen 5 x16 (uses x8)
Rozhraní paměti	128-bit
Takt jádra (MHz)	Extreme Performance: 2535 MHz (MSI Center) Boost: 2527 MHz
Takt paměti (MHz)	28 Gbps
Max připojených displejů	4
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP podpora	Y
Doporučený výkon zdroje (W)	550 W
Digital Maximum Resolution	7680 x 4320
Napájecí kabely	8-pin x 1
Podpora DirectX verze	12 Ultimate
Podpora OpenGL verze	4.6
Rozměry (mm)	197 x 120 x 40 mm
Váha (g)	493 g / 814 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Backplate

A clean-looking backplate reinforces the length of the card.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.