




SPECIFICATIONS

| | |
|------------------------------------|---|
| Marketing Name | GeForce RTX™ 5060 Ti 8G VENTUS 3X OC |
| Model Name | G506T-8V3C |
| Cores | 4608 Units |
| Memory | 8GB GDDR7 |
| Standard sběrnice | PCI Express® Gen 5 x16 (uses x8) |
| Rozhraní paměti | 128-bit |
| Takt jádra (MHz) | Extreme Performance: 2617 MHz (MSI Center) Boost: 2602 MHz |
| Takt paměti (MHz) | 28 Gbps |
| Max připojených displejů | 4 |
| Output | DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| HDCP podpora | Y |
| Doporučený výkon zdroje (W) | 600 W |
| Digital Maximum Resolution | 7680 x 4320 |
| Napájecí kabely | 8-pin x 1 |
| Podpora DirectX verze | 12 Ultimate |
| Podpora OpenGL verze | 4.6 |
| Rozměry (mm) | 304 x 121 x 44 mm |
| Váha (g) | 793 g / 1162 g |

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.




Solid Baseplate

A solid baseplate transfers heat from the GPU to all heat pipes for better cooling.



Backplate

A clean-looking backplate reinforces the length of the card.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.