



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5070 12G VANGUARD SOC
Model Name	G5070-12VGS
Cores	6144 Units
Memory	12GB GDDR7
Standard sběrnice	PCI Express® Gen 5
Rozhraní paměti	192-bit
Takt jádra (MHz)	TBD
Takt paměti (MHz)	28 Gbps
Max připojených displejů	4
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP podpora	Y
Doporučený výkon zdroje (W)	TBD
Digital Maximum Resolution	7680 x 4320
Napájecí kabely	16-pin x 1
Podpora DirectX verze	12 Ultimate
Podpora OpenGL verze	4.6
Rozměry (mm)	337 x 140 x 61 mm
Váha (g)	TBD g / TBD g

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES




HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.




STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Filled Fins

Updated heat pipe pathing has allowed more space for additional heatsink fins.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.