



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G VANGUARD OC
Model Name	G5080-16VGC
Cores	10752 Units
Memory	16GB GDDR7
Standard sběrnice	PCI Express® Gen 5
Rozhraní paměti	256-bit
Takt jádra (MHz)	Extreme Performance: 2715 MHz (MSI Center) Boost: 2700 MHz (GAMING & SILENT Mode)
Takt paměti (MHz)	30 Gbps
Max připojených displejů	4
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP podpora	Y
Doporučený výkon zdroje (W)	850W
Digital Maximum Resolution	7680 x 4320
Napájecí kabely	16-pin x 1
Podpora DirectX verze	12 Ultimate
Podpora OpenGL verze	4.6
Rozměry (mm)	357 x 151 x 66 mm
Váha (g)	1945 g / 2844 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.



Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.



Filled Fins

Updated heat pipe pathing has allowed more space for additional heatsink fins.