



MAG 274UPDF E16M



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G INSPIRE 2X OC
Model Name	G506-8I2C
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060
Interface	PCI Express® Gen 5 x16 (uses x8)
Cores	3840 Units
Core Clocks	Extreme Performance: 2550 MHz (MSI Center) Boost: 2535 MHz
Memory Speed	28 Gbps
Memory	8GB GDDR7
Memory Bus	128-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	145 W
Power connectors	8-pin x1
Recommended PSU	TBD
Card Dimension (mm)	204 x 117 x 41 mm
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.




STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.




Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.