




SPECIFICATIONS

Model Name	GeForce RTX™ 4070 Ti SUPRIM X 12G
Cores	7680 Units
Memory	12GB GDDR6X
Memory Bus	192-bit
Power connectors	16-pin x 1
Recommended PSU	750 W
Motor Gráfico	NVIDIA® GeForce RTX™ 4070 Ti
Bus Standard	PCI Express® Gen 4
Card Dimension (mm)	338 x 142 x 73 mm
DirectX Version Support	12 Ultimate
Reloj de Núcleo	Extreme Performance: 2790 MHz (MSI Center) Boost: 2775 MHz (GAMING & SILENT Mode)
Velocidad de Memoria	21 Gbps
Maximum Displays	4
G-SYNC™ technology	Y
Power consumption (W)	285 W
Soporte HDCP	Y
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
Digital Maximum Resolution	7680x4320
Versión Soportada de OpenGL	4.6
Peso	2019g / 3224g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

The CNC machined nickel-plated copper base captures heat from the GPU and the memory then rapidly transfers it to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Airflow Control

Wave-curved 3.0 fin edges disrupt unwanted airflow harmonics resulting in reduced noise.



Air Antegrade Fin

A section of V-shape heatsink and side-fins work to refocus air resistance at the passthrough.



Aluminum Backplate

Thermal pads beneath the sturdy metal backplate provide additional cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.