# GeForce RTX™ 5060 Ti 16G VENTUS 2X PLUS

## SPECIFICATIONS

| | |
|---|---|
| **Marketing Name** | GeForce RTX™ 5060 Ti 16G VENTUS 2X PLUS |
| **Model Name** | G506T-16V2P |
| **Cores** | 4608 Units |
| **Memory** | 16GB GDDR7 |
| **Memory Bus** | 128-bit |
| **Power connectors** | 8-pin x1 |
| **Recommended PSU** | 600 W |
| **Motor Gráfico** | NVIDIA® GeForce RTX™ 5060 Ti |
| **Bus Standard** | PCI Express® Gen 5 x16 (uses x8) |
| **Card Dimension (mm)** | 227 x 126 x 41 mm |
| **DirectX Version Support** | 12 Ultimate |
| **Reloj de Núcleo** | Extreme Performance: 2587 MHz (MSI Center)<br>Boost: 2572 MHz |
| **Velocidad de Memoria** | 28 Gbps |
| **Maximum Displays** | 4 |
| **G-SYNC™ technology** | Y |
| **Output** | DisplayPort x 3 (v2.1b)<br>HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| **Soporte HDCP** | Y |
| **Power consumption (W)** | 180 W |
| **Digital Maximum Resolution** | 7680 x 4320 |
| **Versión Soportada de OpenGL** | 4.6 |
| **Peso** | 600 g / 862 g |

## FEATURES

**Dual Fan**

Two fans and a huge heatsink ensure a cool and quiet experience for you.

**STORMFORCE FAN**

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.

**Metal Backplate**

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.

**Zero Frozr**

The fans completely stop when temperatures are relatively low, eliminating all noise.

**DrMOS**

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

**Fuse**

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

**MSI Center**

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

**Afterburner**

Take full control with the most recognized and widely used graphics card overclocking software in the world.

## CONNECTIONS

1. DisplayPort
2. HDMI™