



## SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G VENTUS 3X
Model Name	G5060-8V3
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060
Interface	PCI Express® Gen 5 X16 (uses x8)
Core Clocks	Extreme Performance: 2512 MHz (MSI Center) Boost: 2497 MHz
CUDA® CORES	3840 Units
Memory Speed	28 Gbps
Memory	8GB GDDR7
Memory Bus	128-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	145 W
Power connectors	8-pin x1
Recommended PSU	550 W
Card Dimension (mm)	303 x 121 x 41 mm
Weight (Card / Package)	684 g / 1042 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

## CONNECTIONS



1. DisplayPort
2. HDMI™

## FEATURES

### Triple Fan



Three fans and a huge heatsink ensure a cool and quiet experience for you.

### TORX FAN 5.0



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

### Nickel-plated Copper Baseplate



Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.

### Core Pipes



Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.

### Reinforcing Backplate



The reinforcing backplate features a flow-through design that provides additional ventilation.

### Zero Frozr



The fans completely stop when temperatures are relatively low, eliminating all noise.

### DrMOS



DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

### Fuse



Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

### MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

### Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.