

SPECIFICATIONS

Marketing Name	GeForce RTX™ 5070 Ti 16G SHADOW 3X
Model Name	G507T-16S3
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5070 Ti
Interface	PCI Express® Gen 5
Core Clocks	Extreme Performance: 2467 MHz (MSI Center) Boost: 2452 MHz
CUDA® CORES	8960 Units
Memory Speed	28 Gbps
Memory	16GB GDDR7
Memory Bus	256-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	300 W
Power connectors	16-pin x 1 (ATX 3.1 PSU recommended)
Recommended PSU	750 W
Card Dimension (mm)	303 x 121 x 49 mm
Weight (Card / Package)	994 g / 1474 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.




Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.