



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G SHADOW 3X
Model Name	G5080-16S3
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5080
Interface	PCI Express® Gen 5
Core Clocks	Extreme Performance: 2625 MHz (MSI Center) Boost: 2617 MHz
CUDA® CORES	10752 Units
Memory Speed	30 Gbps
Memory	16GB GDDR7
Memory Bus	256-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	360 W
Power connectors	16-pin x 1 (ATX 3.1 PSU recommended)
Recommended PSU	850 W
Card Dimension (mm)	303 x 121 x 49 mm
Weight (Card / Package)	1046 g / 1546 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

Triple Fan



Three fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 5.0



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Nickel-plated Copper Baseplate



Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.

Core Pipes



Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.

Reinforcing Backplate



The reinforcing backplate features a flow-through design that provides additional ventilation.

Zero Frozr



The fans completely stop when temperatures are relatively low, eliminating all noise.

Fuse



Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

DrMOS



DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.