




SPECIFICATIONS

Model Name	GeForce RTX™ 4080 SUPER 16G SUPRIM
繪圖引擎	NVIDIA® GeForce RTX™ 4080 SUPER
科技介面	PCI Express® Gen 4
動態 / 核心時脈(MHz)	Extreme Performance: 2625 MHz (MSI Center) Boost: 2610 MHz (GAMING & SILENT Mode)
Cores	10240 Units
記憶體速度	23 Gbps
Memory	16GB GDDR6X
記憶體介面	256-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
HDCP 支援	Y
功耗(W)	320 W
供電接口	16-pin x 1
建議電源供應(W)	850 W (Min.750 W)
顯示卡尺寸(mm)	336 x 142 x 78 mm
重量 (顯示卡 / 包裝盒)	2372g / 3573g
DirectX 支援版本	12 Ultimate
OpenGL 支援版本	4.6
最大螢幕輸出數量	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.




Airflow Control

Wave-curved 3.0 fin edges disrupt unwanted airflow harmonics resulting in reduced noise.



Aluminum Backplate

Thermal pads beneath the sturdy metal backplate provide additional cooling.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.