GRAPHICS CARD

GeForce RTX™ 3060 VENTUS 2X 12G








SPECIFICATIONS

Model Name	GeForce RTX™ 3060 VENTUS 2X 12G
Cores	3584
Memory	12GB GDDR6
G-SYNC™ technology	Y
Graphics Processing Unit	NVIDIA® GeForce RTX™ 3060
Adaptive Vertical Sync	Y
Interface	PCI Express® Gen 4
Boost / Base Core Clock	Boost: 1777 MHz
Memory Interface	192-bit
Memory Clock Speed (MHz)	15 Gbps
Output	DisplayPort x 3 (v1.4) / HDMI™ x 1 (Supports 4K@120Hz as specified in HDMI™ 2.1)
Virtual Reality Ready	Y
Maximum Displays	4
HDCP Support	Y
DirectX Version Support	12 API
Card Dimension(mm)	235 x 124 x 42 mm
Card Weight (g)	675 g / 1030 g
Power consumption (W)	170W
Recommended PSU (W)	550W
Power Connectors	8-pin x 1

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 3.0

The award-winning MSI TORX Fan 3.0 design creates high static pressure and pushes the limits of thermal performance.

Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.

Thermal Padding

An abundance of thermal pads use any chance for additional heat transfer directly from the components.

Custom PCB

The custom PCB has been engineered with hardened circuits and optimized trace routing for performance and reliability.

Dragon Center

MSI's exclusive Dragon Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

Generated 2024-12-04, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2024 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.© 2024 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.