


SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G INSPIRE 3X OC
Model Name	G5080-16J3C
Cores	10752 Units
Memory	16GB GDDR7
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5080
G-SYNC™ technology	Y
Interface	PCI Express® Gen 5
Digital Maximum Resolution	7680 x 4320
Memory Interface	256-bit
Memory Clock Speed (MHz)	30 Gbps
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Maximum Displays	4
HDCP Support	Y
DirectX Version Support	12 Ultimate
Card Dimension(mm)	288 x 112 x 50 mm
Card Weight (g)	950 g / 1437 g
Power consumption (W)	360W
Recommended PSU (W)	850W
Power Connectors	16-pin x1

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.




Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



Air Antegrade Fin

Fins with a V-shaped cutout are located at the airflow passthrough to improve flow efficiency.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.