



SPECIFICATIONS

Socket	GeForce RTX™ 3090 SUPRIM X 24G
Socket	NVIDIA® GeForce RTX™ 3090
Socket	PCI Express® Gen 4
Socket	10496 Units
Socket	Extreme Performance: 1875 MHz (Dragon Center) Boost: 1860 MHz (GAMING & SILENT Mode)
Socket	19.5 Gbps
Socket	420W
Socket	8-pin x 3
Socket	750 W
Socket	336 x 140 x 61 mm
Socket	1895g / 3197g
Socket	Y
Socket	Y
Socket	7680 x 4320
Marketing Name	GeForce RTX™ 5060 8G GAMING TRIO OC
Memory	8GB GDDR7
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060
Interface	PCI Express® Gen 5 x16 (uses x8)
Core Clock Speed (MHz)	Extreme Performance: 2640 MHz (MSI Center) Boost: 2625 MHz
Memory Interface	128-bit
Memory Clock Speed (MHz)	28 Gbps
OpenGL Version Support	4.6
Maximum Displays	4
HDCP Support	Y
DirectX Version Support	12 Ultimate
Card Dimension(mm)	300 x 125 x 44 mm
Card Weight (g)	797 g / 1206 g
Power consumption (W)	155 W
Recommended PSU (W)	550 W
Digital Maximum Resolution	7680 x 4320
Power Connectors	8-pin x 1

FEATURES



TRI FROZR 4

Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



MSI Center


The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

CONNECTIONS



1. DisplayPort
2. HDMI™