



SPECIFICATIONS

| | |
|----------------------------|---|
| Marketing Name | GeForce RTX™ 5060 8G SHADOW 2X OC |
| Memory | 8GB GDDR7 |
| Output | DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 5060 |
| Interface | PCI Express® Gen 5 x16 (uses x8) |
| Core Clock Speed (MHz) | Extreme Performance: 2535 MHz (MSI Center) Boost: 2527 MHz |
| Memory Interface | 128-bit |
| Memory Clock Speed (MHz) | 28 Gbps |
| OpenGL Version Support | 4.6 |
| Maximum Displays | 4 |
| HDCP Support | Y |
| DirectX Version Support | 12 Ultimate |
| Card Dimension(mm) | 197 x 120 x 40 mm |
| Card Weight (g) | 493 g / 814 g |
| Power consumption (W) | 145 W |
| Recommended PSU (W) | 550 W |
| Digital Maximum Resolution | 7680 x 4320 |
| Power Connectors | 8-pin x 1 |
| Mic-in/Headphone-out | 1/1 |

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.




TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.