

GeForce RTX™ 5060 Ti 16G VENTUS 2X PLUS







SPECIFICATIONS

| Marketing Name | GeForce RTX™ 5060 Ti 16G VENTUS 2X PLUS |
|---------------------------------|--|
| Memory | 16GB GDDR7 |
| Output | DisplayPort x 3 (v2.1b) HDMI [™] x 1 (As specified in HDMI [™] 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 5060 Ti |
| Interface | PCI Express® Gen 5 x16 (uses x8) |
| Core Clock Speed (MHz) | Extreme Performance: 2587 MHz (MSI Center) Boost: 2572 MHz |
| Memory Interface | 128-bit |
| Memory Clock Speed (MHz) | 28 Gbps |
| OpenGL Version Support | 4.6 |
| Maximum Displays | 4 |
| HDCP Support | Y |
| DirectX Version Support | 12 Ultimate |
| Card Dimension(mm) | 227 x 126 x 41 mm |
| Card Weight (g) | 600 g / 862 g |
| Power consumption (W) | 180 W |
| Recommended PSU (W) | 600 W |
| Digital Maximum Resolution | 7680 x 4320 |
| Power Connectors | 8-pin x1 |
| Mic-in/Headphone-out | 1/1 |

CONNECTIONS



- $1.\ \mathsf{DisplayPort}$
- 2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



use

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.