GeForce RTX™ 5060 Ti 16G VENTUS 3X OC


SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 Ti 16G VENTUS 3X OC
Memory	16GB GDDR7
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060 Ti
Interface	PCI Express® Gen 5 x16 (uses x8)
Core Clock Speed (MHz)	Extreme Performance: 2617 MHz (MSI Center) Boost: 2602 MHz
Memory Interface	128-bit
Memory Clock Speed (MHz)	28 Gbps
OpenGL Version Support	4.6
Maximum Displays	4
HDCP Support	Y
DirectX Version Support	12 Ultimate
Card Dimension(mm)	304 x 121 x 44 mm
Card Weight (g)	860 g / 1229 g
Power consumption (W)	180 W
Recommended PSU (W)	600 W
Digital Maximum Resolution	7680 x 4320
Power Connectors	8-pin x 1
Mic-in/Headphone-out	1/1

CONNECTIONS

1. DisplayPort
2. HDMI™

FEATURES

Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Solid Baseplate

A solid baseplate transfers heat from the GPU to all heat pipes for better cooling.

Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.

Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.

DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.