

GeForce RTX™ 5080 16G SUPRIM LIQUID SOC







SPECIFICATIONS

| Marketing Name | GeForce RTX™ 5080 16G SUPRIM LIQUID SOC |
|----------------------------|--|
| Memory | 16 GB GDDR7 |
| Output | DisplayPort x 3 (v2.1b) HDMI [™] x 1 (As specified in HDMI [™] 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| Graphics Processing Unit | NVIDIA [®] GeForce RTX [™] 5080 |
| Interface | PCI Express [®] Gen 5 x 16 |
| Core Clock Speed (MHz) | Extreme Performance: 2760 MHz (MSI Center) Boost: 2745 MHz |
| Memory Interface | 256-bit |
| Memory Clock Speed (MHz) | 30 Gbps |
| OpenGL Version Support | 4.6 |
| Maximum Displays | 4 |
| HDCP Support | <u>Y</u> |
| DirectX Version Support | 12 Ultimate |
| Card Dimension(mm) | Card: 280 x 148 x 51mm Radiator: 394 x 121 x 55mm Tube length: 450mm |
| Card Weight (g) | 2812 g / 4129 g |
| Power consumption (W) | 360 W |
| Recommended PSU (W) | 850 W |
| Digital Maximum Resolution | 7680 x 4320 |
| Power Connectors | 16-pin x 1 (ATX 3.1 PSU recommended) |
| Mic-in/Headphone-out | 1/1 |

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES




SUPERIOR HYBRID COOLING

SUPRIM LIQUID's innovative Hybrid design uses both air cooling with STORMFORCE Fan and liquid cooling to effectively manage heat from the GPU and VRAM.



Advanced Performance Pump

A premium design for optimal flow, delivering automotive-grade coolant to ensure the SUPRIM LIQUID stays cool and performs efficiently.





The 360 mm aluminum radiator ensures efficient cooling, while the STORMFORCE fans enhance airflow and simplifies cable management for a tidy installation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Micro-Fin Copper Base

A copper base with fine micro-fins immersed in the liquid stream effectively transfers heat away from the VRAM and GPU.



Durable Tubing with Scratch-proof Cover

Braided PVC tubes resist permeation and stay flexible, while the scratch-proof cover enhances durability during SUPRIM LIQUID installation.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



MSI Center