GeForce RTX™ 5080 16G VANGUARD SOC







SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G VANGUARD SOC
Memory	16GB GDDR7
Output	DisplayPort x 3 (v2.1b) HDMI [™] x 1 (As specified in HDMI [™] 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5080
Interface	PCI Express [®] Gen 5
Core Clock Speed (MHz)	Extreme Performance: 2745 MHz (MSI Center) Boost: 2730 MHz (GAMING & SILENT Mode)
Memory Interface	256-bit
Memory Clock Speed (MHz)	30 Gbps
OpenGL Version Support	4.6
Maximum Displays	4
HDCP Support	Υ
DirectX Version Support	12 Ultimate
Card Dimension(mm)	357 x 151 x 66 mm
Card Weight (g)	1945 g / 2844 g
Power consumption (W)	360W
Recommended PSU (W)	850W
Digital Maximum Resolution	7680 x 4320
Power Connectors	16-pin x 1
Mic-in/Headphone-out	1/1

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES



HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.



Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Updated heat pipe pathing has allowed more space for additional heatsink fins.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.