

SPECIFICATIONS

| | |
|--------------------------------------|---|
| Cores | 5888 Units |
| Memory | 12GB GDDR6X |
| Card Dimension (mm) | 242 x 125 x 43 mm |
| Velocità Core Clock (MHz) | Extreme Performance: 2520 MHz (MSI Center) Boost: 2505 MHz |
| Velocità Memory Clock (MHz) | 21 Gbps |
| Schermi massimi | 4 |
| Output | DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a) |
| Consumi Energetici (W) | 200 W |
| Alimentatore raccomandato (W) | 650 W |
| Digital Maximum Resolution | 7680 x 4320 |
| Connettori di alimentazione | 8-pin x 1 |
| Versione DirectX Supportata | 12 Ultimate |
| Versione OpenGL Supportata | 4.6 |
| Peso | 663 g / 959 g |

FEATURES



EZ PCIe Clip II

Allows for easy removal of the graphics card by pressing the tail-like lock with one finger, even in the cramped case spaces.



EZ PCIe Release

A simple press of a button to effortlessly lock or unlock the PCIe slot, simplifying the installation and removal of the graphics card.



EZ M.2 Shield Frozr II


The new tool-less design makes installing or removing your M.2 SSD and Shield Frozr much easier



Dual LAN

Dual premium network solution for both Intranet and Internet, offering a smooth gaming experience for effective network connection

CONNECTIONS



1. DisplayPort
2. HDMI™