


SPECIFICATIONS


Cores	16384 Units
Memory	24GB GDDR6X
Graphics Engine	NVIDIA® GeForce RTX™ 4090
Bus Standard	PCI Express® Gen 4
Interfaccia Memoria	384-bit
Velocità Core Clock (MHz)	Extreme Performance: 2610 MHz (MSI Center) Boost: 2595 MHz (GAMING & SILENT Mode)
Velocità Memory Clock (MHz)	21 Gbps
Schermi massimi	4
Supporto HDCP	Y
Consumi Energetici (W)	Silent mode: 450W Gaming mode: 480W
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
Alimentatore raccomandato (W)	1000W (Min. 850W)
Digital Maximum Resolution	7680x4320
Connettori di alimentazione	16-pin x 1
Versione DirectX Supportata	12 Ultimate
Versione OpenGL Supportata	4.6
Dimensioni scheda (mm)	Card: 280 x 140 x 43 mm radiator + fan: 274 x 121 x 55 mm Tube length: L470 ± 10 x D11.2 mm
Peso	2353 g / 3837 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



Superior Cooling

The GPU is kept cool by closed loop liquid cooler while the memory and VRM's are cooled by a radial fan.




TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Micro-Fin Copper Base

A copper base with fine micro-fins immersed in the liquid stream effectively transfers heat away from the VRAM and GPU.



Aluminum Heat Radiator

Easy to install 240mm black aluminum radiator to reduce fan demand and dissipate heat efficiently.



Quick And Easy Installation

Upgrade to the power of liquid-cooled graphics in one minute or less.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.