




SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G GAMING TRIO OC WHITE
Cores	10752 Units
Memory	16GB GDDR7
Card Dimension (mm)	338 x 140 x 50 mm
Velocità Core Clock (MHz)	Extreme Performance: 2715 MHz (MSI Center) Boost: 2700 MHz (GAMING & SILENT Mode)
Velocità Memory Clock (MHz)	30 Gbps
Schermi massimi	4
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Consumi Energetici (W)	360 W
Alimentatore raccomandato (W)	850 W
Digital Maximum Resolution	7680 x 4320
Connettori di alimentazione	16-pin x 1 (ATX 3.1 PSU recommended)
Versione DirectX Supportata	12 Ultimate
Versione OpenGL Supportata	4.6
Peso	1362 g / 1885 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

TRI FROZR 4



Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.

STORMFORCE FAN



Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.

Nickel-plated Copper Baseplate



Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.

Core Pipes



Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.

Wave Curved 4.0



Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.

Air Antegrade Fin 2.0



The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.

Metal Backplate



A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.

Dual BIOS



Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.