



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G GAMING OC
製品型番	G5060-8GC
搭載GPU	NVIDIA® GeForce RTX™ 5060
コア数	3840 Units
コアクロック [MHz]	Extreme Performance: 2640 MHz (MSI Center) Boost: 2625 MHz
メモリアイプ*2	8GB GDDR7
メモリスピード	28 Gbps
サイズ	248 x 135 x 41 mm
メモリバス幅 [bit]	128-bit
HDCPサポート	Y
消費電力 (W)	155 W
補助電源コネクタ*3	8-pin x 1
推奨電源ユニット容量 (W)	550 W
重さ (g)	649 g / 966 g
DirectX対応バージョン	12 Ultimate
OpenGL対応バージョン	4.6
最大同時出力画面数	4
映像出力端子	DisplayPort x 3 (v2.1b) HDMI™ x 1 (Supports 4K@480Hz HDR, 8K@120Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1b)
G-SYNC™ technology	Y
最大画面解像度 (デジタル)	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Twin Frozr 10

Experience superior cooling and quieter performance with MSI's enhanced fan blade design.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.