


SPECIFICATIONS

Marketing Name	GeForce RTX™ 5070 Ti 16G INSPIRE 3X OC
製品型番	G507T-16I3C
搭載GPU	NVIDIA® GeForce RTX™ 5070 Ti
コア数	8960 Units
コアクロック [MHz]	Extreme Performance: 2497 MHz (MSI Center) Boost: 2482 MHz
メモリアイプ*2	16GB GDDR7
メモリスピード	28 Gbps
メモリバス幅 [bit]	256-bit
HDCPサポート	Y
消費電力 (W)	300W
補助電源コネクタ*3	16-pin x 1
推奨電源ユニット容量 (W)	750W
重さ (g)	904 g / 1360 g
サイズ	288 x 112 x 50 mm
DirectX対応バージョン	12 Ultimate
OpenGL対応バージョン	4.6
最大同時出力画面数	4
映像出力端子	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
G-SYNC™ technology	Y
最大画面解像度 (デジタル)	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.




Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Air Antegrade Fin

Fins with a V-shaped cutout are located at the airflow passthrough to improve flow efficiency.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.