

GeForce RTX™ 4070 Ti GAMING X TRIO WHITE 12G









SPECIFICATIONS

Model Name	GeForce RTX™ 4070 Ti GAMING X TRIO WHITE 12G
Graphics Processing Unit	NVIDIA [®] GeForce RTX™ 4070 Ti
Interface	PCI Express [®] Gen 4
Cores	7680 Units
Core Clocks	Extreme Performance: 2760 MHz (MSI Center) Boost: 2745 MHz (GAMING & SILENT Mode)
Memory Speed	21 Gbps
Memory	12GB GDDR6X
Memory Bus	192-bit
Recommended PSU	700W
Card Dimension (mm)	337 x 140 x 62 mm
Weight (Card / Package)	1599g/2580g
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320
Power consumption (W)	285W
HDCP Support	Y
Output	DisplayPort x 3 (v1.4a) HDMI [™] x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI [™] 2.1a)
Power Connectors	16pin x 1
OpenGL Version Support	4.6

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.





The CNC machined nickel-plated copper base captures heat from the GPU and the memory then rapidly transfers it to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Anti Bending

A die-cast anti-bending plate reinforces the card while thermal pads allow cooling to reach critical component underneath.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.