

SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G SHADOW 3X OC
Model Name	G5080-16S3C
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5080
Interface	PCI Express® Gen 5
Cores	10752 Units
Core Clocks	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz
Memory Speed	30 Gbps
Memory	16GB GDDR7
Memory Bus	256-bit
Recommended PSU	850 W
Card Dimension (mm)	303 x 121 x 49 mm
Weight (Card / Package)	1046 g / 1546 g
Maximum Displays	4
G-SYNC® technology	Y
Power consumption (W)	360 W
Digital Maximum Resolution	7680 x 4320
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power Connectors	16-pin x 1
OpenGL Version Support	4.6

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.




Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.