



SPECIFICATIONS

| | |
|-----------------------------------|--|
| Marketing Name | GeForce RTX™ 5090 32G SUPRIM LIQUID SOC |
| Model Name | G5090-32SLS |
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 5090 |
| Interface | PCI Express® Gen 5x 16 |
| Cores | 21760 Units |
| Core Clocks | Gaming Mode: Extreme Performance: 2580 MHz (MSI Center) Boost: 2565 MHz Silent Mode: Extreme Performance: 2527 MHz (MSI Center) Boost: 2512 MHz |
| Memory Speed | 28 Gbps |
| Memory | 32GB GDDR7 |
| Memory Bus | 512-bit |
| Recommended PSU | 1000 W |
| Card Dimension (mm) | Card: 280 x 148 x 51mm Radiator: 394 x 121 x 55mm Tube length: 450mm |
| Weight (Card / Package) | 2969 g / 4273 g |
| Maximum Displays | 4 |
| G-SYNC® technology | Y |
| Power consumption (W) | Gaming mode: 600 W Silent mode: 575 W |
| Digital Maximum Resolution | 7680 x 4320 |
| Output | DisplayPort x 3 (2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR) |
| HDCP Support | Y |
| Power Connectors | 16-pin x 1 |
| OpenGL Version Support | 4.6 |

CONNECTIONS

FEATURES



SUPERIOR HYBRID COOLING

SUPRIM LIQUID's innovative Hybrid design uses both air cooling with STORMFORCE Fan and liquid cooling to effectively manage heat from the GPU and VRAM.



Advanced Performance Pump

A premium design for optimal flow, delivering automotive-grade coolant to ensure the SUPRIM LIQUID stays cool and performs efficiently.



Patented Water Block Design

The patented water block features a special waterway layout and CNC-machined copper base that cools the GPU and VRAM, helping to lower temperatures.



360 mm Aluminum Radiator

The 360 mm aluminum radiator ensures efficient cooling, while the STORMFORCE fans enhance airflow and simplifies cable management for a tidy installation.




STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Micro-Fin Copper Base

A copper base with fine micro-fins immersed in the liquid stream effectively transfers heat away from the VRAM and GPU.



Durable Tubing with Scratch-proof Cover

Braided PVC tubes resist permeation and stay flexible, while the scratch-proof cover enhances durability during SUPRIM LIQUID installation.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



그래픽카드

GeForce RTX™ 5090 32G SUPRIM LIQUID SOC



1. DisplayPort
2. HDMI™