




SPECIFICATIONS

Memory	16GB GDDR6
Motor de gráficos	NVIDIA® GeForce RTX™ 4060 Ti
Norma Bus	PCI Express® Gen 4 x 8
Interfaz de Memoria	128-bit
Velocidad clock núcleo (MHz)	Extreme Performance: 2685 MHz (MSI Center) Boost: 2670 MHz
Velocidad clock memoria (MHz)	18 Gbps
Máximo de pantallas	4
Tecnología G-SYNC™	Y
Salida	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI 2.1a)
Soporte HDCP	Y
Consumo (W)	165W
Alimentación recomendada (W)	550W
Resolución máxima digital	7680 x 4320
Conectores de alimentación	8-pin x 1
Soporte DirectX Versión	12 Ultimate
Soporte OpenGL Versión	4.6
Dimensiones (mm)	307 x 125 x 46 mm

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.




TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.