



## SPECIFICATIONS

Socket	4.6
Socket	8-pin x 2
Socket	12 API
Socket	1
Socket	1
Socket	8GB GDDR6
Socket	Y
Socket	Y
Socket	5888 Units
Socket	GeForce RTX™ 3070 VENTUS 2X OC
Socket	DisplayPort x 3 (v1.4a) / HDMI™ 2.1 x 1
Socket	Y
Socket	7680x4320
Socket	650W
Socket	PCI Express® Gen 4
Socket	Y
Socket	14 Gbps
Socket	220W
Socket	256-bit
Socket	1755 MHz
Socket	NVIDIA® GeForce RTX™ 3070
Socket	232 x 124 x 52 mm
Socket	832g / 1255g
Socket	1/1
Socket	4
Memory	4GB GDDR6
Motor de gráficos	Radeon™ RX 6400
Norma Bus	PCI Express® Gen 4 x 4
Interfaz de Memoria	64-bit
Velocidad clock núcleo (MHz)	Boost: Up to 2321 MHz Game: Up to 2039 MHz
Velocidad clock memoria (MHz)	16 Gbps
Máximo de pantallas	2
FreeSync™ Technology	Y
Consumo (W)	53W
Soporte HDCP	Y

## FEATURES




### Custom PCB

The custom PCB has been engineered with hardened circuits and optimized trace routing for performance and reliability.



### Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.



### Thermal Padding

An abundance of thermal pads use any chance for additional heat transfer directly from the components.



### MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

<b>Salida</b>	DisplayPort x 1 (v1.4a) / HDMI™ x 1 (Supports 4K@120Hz/8K@60Hz and VRR as specified in HDMI™ 2.1)
<b>Alimentación recomendada (W)</b>	350W
<b>Resolución máxima digital</b>	7680 x 4320
<b>Virtual Reality Ready</b>	Y
<b>Conectores de alimentación</b>	N/A
<b>Soporte DirectX Versión</b>	12 API
<b>Soporte OpenGL Versión</b>	4.6
<b>Dimensiones (mm)</b>	172 x 112 x 39 mm

## CONNECTIONS

