
TARJETAS GRÁFICAS

GeForce RTX™ 5060 Ti 16G VENTUS 2X OC PLUS








SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 Ti 16G VENTUS 2X OC PLUS
Core Clocks	Extreme Performance: 2617 MHz (MSI Center) Boost: 2602 MHz
Núcleos	4608 Units
Memoria	16GB GDDR7
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Motor de gráficos	NVIDIA® GeForce RTX™ 5060 Ti
Máximo de pantallas	4
Tecnología G-SYNC™	Y
Alimentación recomendada (W)	TBD
Resolución máxima digital	7680 x 4320
Conectores de alimentación	8-pin x1
Soporte OpenGL Versión	4.6
Dimensiones (mm)	227 x 127 x 41 mm

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.

STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.

Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.

Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.

DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

Generated 2026-11-06, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.© 2026 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.