



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5070 12G SHADOW 2X OC
Core Clocks	Extreme Performance: 2557 MHz (MSI Center) Boost: 2542 MHz
Núcleos	6144 Units
Memoria	12GB GDDR7
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Motor de gráficos	NVIDIA® GeForce RTX™ 5070
Máximo de pantallas	4
Tecnología G-SYNC™	Y
Alimentación recomendada (W)	650 W
Resolución máxima digital	7680 x 4320
Conectores de alimentación	16-pin x 1
Soporte OpenGL Versión	4.6
Dimensiones (mm)	231 x 126 x 50 mm

CONNECTIONS



FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.




Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.